L150 Tack Tank





The 150 Tack Distributor ideally serves the paving contractor dedicated to smaller projects. With a conservative 150 gallon capacity tank, this solution still contains many of the features and functionality of the larger units. Inclusive of a powerful Honda engine, the user-friendly design can either be trailer or skid mounted. Multiple additional options including remote in-cab controls or overnight heating can further enhance the end user's experience.

Performance Features:

- 150 Gallon (567.8 I) Capacity Tank
- 4.8 hp (3.6 kw) Honda Engine
- 6' (1.8 m) Wand with On/Off Valve
- 40' (12.19 m) Heavy-Duty Recoil Hose Reel
- · 3,194 lbs (1,448 kg) Loaded Weight
- 1" (25 mm) Rear Tank Sampling Valve
- One 300,000 BTU Propane Burner
- Trailer-Mounted or Skid-Mounted Configurations
- Electric brakes
- Emergency Brake-Away System
- Optional Accessories Available







L150 Tack Distributor Specifications



| Tank Size | 150 gallons (567.8 l) |
|---------------------------------------|---|
| Dimensions (Trailer Configuration) | - Length: 10' 6" (3.22 m) - Width: 6' 6" (1.98 m) - Height: 5' 9" (1.76 m) - Shipping Weight: 1,519 lbs (689 kg) |
| Dimensions (Skid Configuration) | - Length: 7' 6" (2.29 m) - Width: 4' 3" (1.28 m) - Height: 4' 9" (1.45 m) |
| Engine | Honda – 4.8 hp (3.6 kw) |
| Capacities | - Fuel: 1 gallon (3.79 I) |
| Tank Dimensions | - Length: 30.75" (.78 m) - Width: 54.125" (1.37 m) - Height: 36.25" (.92 m) |
| Asphalt Pump | - Specially designed 7 gallons per minute (26.5 lmp) pump |
| Heat System | - One 300,000 BTU propane burner - One start burner - 40 lbs (18.1 kg) propane fuel tank |
| Temperature Gauge | - 50 - 300° F (10 - 149° C) - Adjustable angle faceplate |
| Flush Tank | - 7 gallons (26.5 I) tank with suck back valve |
| Hose and Reel | 5" x 40' (13 mm x 12.19 m) heavy-duty recoil hose reel |

| Wand | - 6' (1.829 m) wand with cold handles - On/off valve - Removable spray tip |
|---------------------------------|---|
| Manhole | - 20" (508 mm) diameter - 10" (254 cm) diameter fill hole - 3 psi (2.1 bar) pressure relief |
| Clean Out | - 4" (102 mm) |
| Sampling Valve | - 1" (25 mm) |
| Additonal Standard Equipment | - Waste bucket mount (trailer only)- 1" rear tank return- 2" in-tank overflow |
| Optional Equipment | Engines - Honda gas - 4.8 hp (3.6 kW) electric start - Hatz diesel - 7.2 hp (5.4 kW) pull start or electric start Fuel: 1.32 gallons (5.0 l) Heat Systems - Diesel Burner One 300,000 BTU diesel burner (only available with electric start engines) 7 gallon (26.5 l) fuel tank Auto ignition diesel burner with outfire - Overnight Heat 120 volt/1000 watt Immersion element Spray bar - Spray width: 12' (3.65 m) - Spray Bar Controls: In-truck wireless remote controls (requires spray bar option) - Spray bar lift with wireless remote control Insulated Tank 2-5/16" ball hitch |





