



ENGINE

Model	Cummins L9
Emissions level	Tier 4 Final
Number of cylinders	6
Displacement	543 in ³ (8.9 L)
Horsepower @ 1,800 RPM:	Net 325 hp (242 kw)
Peak engine torque @ 1,400 RPM:	1,125 lb-ft (1 526 Nm)

DRIVETRAIN

Loading - front axle:		
	4WD	11,797 lb (5 351 kg)
	AWD	12,344 lb (5 599 kg)
Loading - rear axle/tandem:		
	4WD	31,270 lb (14 184 kg)
	AWD	32,245 lb (14 626 kg)
Travel speeds:		
	Forward	Reverse
	mph (kph)	mph (kph)
1st	2 (3.8)	2 (3.7)
2nd	3 (5.5)	3 (5.3)
3rd	5 (8.2)	5 (7.9)
4th	7 (12.1)	7 (11.6)
D	0-28 (0-45)	0-28 (0-45)
Top speed forward/reverse:		28 (45)

DRIVETRAIN

Manufacturer and model	ZF CP290
Transmission description	cPower
Number of speeds - forward	Infinite
Number of speeds - reverse	Infinite
Front axle:	Heavy duty welded fabrication with integrated lean bar lock.
Final drive:	Inboard-mounted planetary sealed in cooled, filtered oil.
Brakes:	Foot-controlled, hydraulically operated, multiple wet-disc brakes sealed in pressurized, cooled, filtered oil. Both independent systems effective on all 4 tandem wheels.
Primary and secondary brakes:	Hydraulically actuated, inboard of tandem pivot, self-adjusting, sealed in cooled and filtered oil, multi-disc (ISO 3450 compliant).
Park brake:	Automatically spring applied, hydraulically released, oil cooled, self-adjusting (ISO 3450 compliant).
Front axle	High strength, welded steel
Oscillation	32° each direction
Wheel lean	20° left/right
Differential:	Spiral bevel gear system, hydraulically actuated with a clutch-type mechanism, allowing differential lock engagement while the machine is in motion. It can be applied in both manual and automatic differential lock modes.
Tandem axle oscillation	30° (Total)
Steering:	Hydraulic frame articulation for maneuverability and productivity, crab steering reduces side drift, positions tandems on firm ground and increases side-slope stability.
Tire size - standard	20.5R25
Service brake type	Multiple wet discs
Service brake actuation	Hydraulic
Ground clearance front axle	23.8 in (605 mm)
HYDRAULICS	
Type	Variable displacement axial piston pump
Pump displacement	100 cc / rev
Pump flow	58 gpm (220 L / min)
Relief pressure	2,750 psi (18 961 kPa)

OPERATOR ENVIRONMENT

ROPS/FOPS certified (ISO 3471, ISO 3449) heated, Air conditioned and defrosted; 7 in Multifunction color display screen with machine usage reports, Fault codes and alarms; Push button start ignition; Dual side cab access; Adjustable operator's console and controls, steering wheel; Air suspension seat with seat belt and adjustable armrests; Dome light; Heated exterior rearview mirrors; Front and rear backup camera with dedicated display screen, Sliding side window, Cup holder; cooler storage box; USB outlet; Bluetooth® radio; Steps - left/right; Front and rear windshield wiper; Front and rear windshield washer; Rear window defroster.

The ventilation system circulates both outside and inside air through filters for a clean working environment. Built in defroster vents direct air flow for effective window de-fogging/de-icing.

OPERATING WEIGHT

16 ft moldboard, 20.5R25 Michelin XTLA tires, push block, and rear ripper with 7 teeth:	
4WD	49,688 lb (22 538 kg)
AWD	51,209 lb (23 228 kg)
Weight, front axle:	
4WD	13,805 lb (6 262 kg)
AWD	14,352 lb (6 510 kg)
Weight, rear axle:	
4WD	35,882 lb (16 276 kg)
AWD	36,857 lb (16 718 kg)

CIRCLE

Circle side shift	31 in (789 mm)
Frame circle diameter	59 in (1 500 mm)
Circle drive:	Hydraulic geroler motor driving a reduction worm box with overload wetplate clutch.
Circle type precision circle:	Sealed and lubricated slewing bearing, requiring no adjustment. Mounted between the drawbar and circleframe, which are welded and machined structures.
Circle rotation	360°
Steering angle	48°
Turning radius - minimum	23 ft 8 in (7.22 m)
Frame articulation (each way)	22°

SERVICE CAPACITIES

Diesel Exhaust Fluid (DEF)	10.6 gal (40 L)
Hydraulic system	31.7 gal (120 L)
Cooling system	9.8 gal (37 L)
Engine oil	6.1 gal (23 L)
Transmission fluid	12.4 gal (47 L)
Axle	8.5 gal (32 L)
Tandem housing (each side)	19.8 gal (75 L)
Circle gearbox	1.3 gal (5 L)

NOTE: Measurements in U.S. gallons.

MOLDBOARD / BLADE

High strength welded construction, using wear resistant high carbon steel materials. Underlays/overlays and cutting edges can be exchanged left to right. Moldboard bronze guides are easily replaceable and adjustable for precision.

Width - moldboard	16 ft (4 880 mm)
Height - moldboard	27 in (686 mm)
Thickness - moldboard combination	7.8/9.8 in (20/25 mm)
Moldboard sideshift - right	27 in (685.5 mm)
Moldboard sideshift - left	27 in (685.5 mm)
Shoulder reach	8 ft 2 in (2 478 mm)
Hydraulic blade tip - forward	44°
Hydraulic blade tip - rearward	3°
Moldboard - lift above ground	19.3 in (490 mm)
Moldboard - arc radius	16.8 in (426 mm)
Throat clearance	3.4 in (87 mm)
Bank angle	90°

Blade pull at maximum operating weight:

4WD	34,723 lb (15 750 kg)
AWD	49,604 lb (22 500 kg)

CUTTING EDGE

Description:
Through hardened Boron steel edge.

Thickness	.7 in (19 mm)
Width	8 in (203 mm)

ELECTRICAL

System voltage	24V
Number of batteries	2
Battery capacity	1 350 CCA
Alternator	120 amp
Number of LED worklights	8
Number of engine bay lights	3
Turn signal lights	Front & rear

ALL WHEEL DRIVE OPTION

Front wheel drive	
Hydrostatic drive: Variable displacement pumps with auto shifting 2 speed motors.	
Independent left and right hydraulic circuits.	
Freewheeling mode: Engages automatically when system is inactive for improved efficiency.	
Inching mode for fine, slow speed maneuvering.	
Precision mode	Front wheel only drive
Pumps	Rexroth
Pump displacement	3.4 in ³ (53 cm ³)
Front wheel motors	Poclain
Motor displacement	137 in ³ (2 238 cm ³)
Reduction	None
AWD max speed	22 mph (35 kph)
Precision mode max speed	6 mph (10 kph)


REAR RIPPER & SCARIFIER

Description:
Parallel linkage, with maintenance free bearings, hydraulic float and integrated tow hitch 5.

Width of cut: Ripper	8 ft 4 in (2 550 mm)
Max number of shanks/teeth: Ripper	7
Lift above ground: Ripper	28 in (712 mm)
Maximum depth: Ripper	11.89 in (302 mm)
Ripper pry-out force (hydraulic limit):	56,218 lb (25 500 kg)
Ripper penetration force (hydraulic limit):	22,249 lb (10 092 kg)
Shank size: Ripper	2.3 × 5.4 in (58 × 137 mm)

MID SCARIFIER

Type:	Radial arm linkage with maintenance free bearings, underslung lift cylinder and hydraulic float. V-type scarifier beam with 3 pitch angle positions.
Width of cut	46.8 in (1 189 mm)
Number of shanks/teeth	12
Lift above ground	11.8 in (300 mm)
Max depth	9.5 in (241 mm)
Shank spacing	4.5 in (114 mm)
Shank size	1 × 3.1 in (27.5 × 78 mm)



Line drawings are for illustrative purpose only and may not be exact representation of unit.

DIMENSIONS

A. Height to top of cab	10 ft 9 in (3 266 mm)
B. Height - exhaust	9 ft 11 in (3 029 mm)
C. Height - blade lift cylinders	9 ft 11 in (3 015 mm)
D. Height - beacon light	11 ft 3 in (3 438 mm)
E. Front axle centre to blade	8 ft 6 in (2 580 mm)
F. Tandem axle wheel centres	5 ft 2 in (1 567 mm)
G. Front axle centre to tandem axle pivot	20 ft 7 in (6 272 mm)
H. Front axle centre to artic centre	17 ft 8 in (5 392 mm)
I. Length - overall without pushblock and ripper	30 ft 1 in (9 228 mm)
J. Length - overall with pushblock	30 ft 8 in (9 353 mm)
K. Length - overall with pushblock and ripper	33 ft 3 in (10 138 mm)
L. Width over tire 20.5R25	9 ft 0 in (2 743 mm)
M. Width over blade - 14 ft	14 ft 0 in (4 273 mm)
M. Width over blade - 16 ft	16 ft 0 in (4 883 mm)
N. Width over mirrors - operating position	7 ft 3 in (2 212 mm)
O. Width over ripper	8 ft 4 in (2 550 mm)
P. Width transport position - 14 ft blade	9 ft 9 in (2 970 mm)
P. Width transport position - 16 ft blade	11 ft 1 in (3 380 mm)

STANDARD EQUIPMENT

OPERATOR ENVIRONMENT

ROPS/FOPS certified
Deluxe Cab with HVAC
Heated air suspension seat
Electro-Hydraulic Controls
Auto articulate function
Auto blade control
Push button ignition start
Selectable operator code
Economy (ECO) mode
Sealed switch module (SSM)
Sealed display controller (SDC)
Machine presets
Hydraulics lock switch
Emergency stop button
Diagnostics port

ENGINE

Cummins L9 Engine
Selective catalytic reduction (SCR)
Diesel particulate filter (DPF)
Block heater

MOLDBOARDS / CIRCLE

16 ft × 27 in (4 877 × 686 mm)
Protected circle with sealed slew bearing
Slip clutch
Blade impact absorption system

TIRES

20.5R25 Michelin XTLA

ELECTRICAL

Rear and front cameras
Reverse backup alarm
LED worklights and headlights
Engine bay lights
Rotating beacon light
Rear mounted cooling module with
hydraulically driven reversing fan
(2) 12V batteries (1,350 CCA)
Battery jump start terminal
Battery electrical disconnect switch

HYDRAULICS

Left-hand side controls: Blade and
machine controls, ripper controls and
1 auxiliary controls
Right-hand side controls: Blade and
machine controls, mid scarifier controls
and 3 auxiliary controls

DRIVETRAIN

Continuous Variable (CVT) Transmission
Auto speed control
Tandem drive system (4WD)
Automatic/Manual differential lock
Inboard planetary axles
Transmission oil cooler
Hydraulic wet disc brakes
Spring-applied hydraulic release
parking brake

OTHER

Rear and front fenders
Tow hitch
Front push block
MyCASEConstruction Telematics
includes hardware and up to 7-year
data subscription

OPTIONAL EQUIPMENT

OPERATOR ENVIRONMENT

Cab air precleaner
AWD selection controller
Rear window heating

MOLDBOARDS

14 ft × 27 in (4 267 × 686 mm)
Reverse overlay bits

HYDRAULICS

Left-hand side controls: Blade and
machine controls, ripper controls and
2 auxiliary controls
Right-hand side controls: Blade and
machine controls, mid scarifier controls
and 4 auxiliary control

ATTACHMENTS

Rear ripper - 7 shanks
Mid mount scarifier

DRIVETRAIN

All Wheel Drive (AWD)
Precision mode (AWD) front wheel
speed adjustment
Inching pedal/Inching mode (AWD)

OTHER

Various tires available (including snow tires)
Engine air intake extension

CaseCE.com

©2026 CNH Industrial America LLC. All rights reserved. CASE is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. CNH Industrial Capital is a trademark in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Printed in U.S.A. Contains 10% post-consumer fiber.

IMPORTANT: CASE Construction Equipment Inc. reserves the right to change these specifications without notice and without incurring any obligation relating to such change. Availability of some models and equipment builds vary according to the country in which the equipment is used. The illustrations and text may include optional equipment and accessories and may not include all standard equipment. Your CASE dealer/distributor will be able to give you details of the products and their specifications available in your area.



CASE Construction Equipment is biodiesel-friendly. NOTE: All engines meet current EPA emissions regulations. All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.



Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs and use any safety features provided.